

# SAFETY SPRAY SHIELDS

FlangeGuards SUREBAND





## SUREBAND SAFETY SPRAY SHIELDS

### **Applications**

- » Spray shields are used to convert dangerous leaks and sprays into safe, manageable releases.
- » Spray shields are safety devices that provide added levels of protection for plant personnel and assets.
- » Spray shields can be used to provide protection on gasketed flanged joints, screwed connections, valve bonnets, filters, expansion joints, and any other components that could pose a leakage risk.





#### **Dimensions**

- To fit ASME B16.5 flanges; 1/2" thru 24" Classes 150, 300 and 600
- » Larger or custom sizes available on request.

#### **Properties**

- The open ended shield design ensures that no leaking product remains trapped within the shield itself.
- » The mechanical latch or hook & loop attachment method provides a quick means to install and remove the shields.

- » No tie cords or additional tools are required to install the shields.
- » Litmus paper patches are incorporated into the shields to provide a visual indication of joint leakage in chemical applications.
- » For smaller flanges sizes, universally sized shields can be fitted to a number of different flange sizes or pressure classes.

#### **Materials**

- » SUREBAND Clear PTFE used with aggressive chemical media.
- » SUREBAND Steel SS 316 stainless steel used with higher temperature and pressure processes.
- » Pressure Diffusion Technology (PDT) multilayered mesh is used with both shield varieties to diffuse pressure from sprays or leaks, and prevents mist formation.







SUREBAND'Steel

#### **KLINGER Thermoseal**

2350 Campbell Road, Sidney, Ohio 45365 Tel: +1 937 498 2222

3803 S. Sam Houston Parkway W., Houston, Texas 77053

Tel: +1 713 997 8111